


Rapidaptor Bit Holders



EAN:	4013288101242	Size:	109x40x40 mm
Part number:	05052504001	Weight:	39 g
Article number:	889/4 R	Country of origin:	CZ
		Customs tariff number:	84661038

- Rapidaptor technology for rapid bit change
- Rapidaptor universal holder for bits with 1/4" hexagon drive, magnetic
- 1/4" hexagon drive

Rapidaptor universal holder for bits with 1/4" external hexagon drive as per DIN ISO 1173-C 6.3 and E 6.3 (ISO 1173). The Rapidaptor allows mounting the bits without using the sleeve. The bit is removed by simply pushing it forward - for lightning-fast bit changes, even with just one hand. The strong permanent magnet holds the bits firmly. 1/4" hexagonal, suitable for screwdriver machines with mounting as per DIN ISO 1173-F 6.3.

Web link


https://products.wera.de/en/bits_holders_adaptors_and_sets_holders_adaptors_connectors_rapidaptor_bit_holders_889_4_r.html

Wera - 889/4 R
05052504001 - 4013288101242

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

Rapidaptor Bit Holders

Magnetic




Bit holders, magnetic, for easier application of the screw

Rapidaptor holder



Rapid bit change without needing any additional tools. One-hand operation with a freely spinning sleeve for simplified guidance of the tool. Also available in a BiTorsion design.

Chuck-all




The Rapidaptor quick-release chucks hold 1/4" DIN ISO 1173-C 6,3 and E 6,3 as well as Wera series 1 and 4 bits.

Single-hand function




Every function of the Rapidaptor quick-release chuck, such as inserting or releasing bits, can be carried out with one hand. This is faster, more economical and more ergonomic. There are no unnecessary manoeuvres.

Rapid-in and self-lock




The bit can be pushed into the adaptor without moving the sleeve. The lock is activated automatically as soon as the bit is applied to the screw. Bits are held securely and wobble-free.

Rapid-out



Simply push the sleeve forward to change the bit. The spring mechanism lifts the bit off the magnet and unlocks the tool. The bit can be easily removed. The rapid-out function makes it easy to remove even the smallest bits without extra tools.

Rapid-spin



The free-turning sleeve allows screw steadying at the start of the screwdriving process. This makes it easier to apply the tool to the screw and prevents slipping. It can also be used as a short extension for 1/4" applications e.g. in combination with the Wera Zyklop Ratchets.

Further versions in this product family:

					
	inch	mm	inch	inch	mm
05052504001	1/4"	100	4"	1/4"	15.0

Web link

https://products.wera.de/en/bits_holders_adaptors_and_sets_holders_adaptors_connectors_rapidaptor_bit_holders_889_4_r.html

Wera - 889/4 R
05052504001 - 4013288101242

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de